

BCS-B-NVR0401-4P

4 channel 1 HDD network recorder with built-in PoE switch



ONVIF®

Key features:

- Display and record 4 IPC with max resolution 8Mpx
- Compression H.265+/H265/H.264+/H.264
- Max incoming bandwidth 40Mbps, outgoing 80Mbps
- Synchronous HDMI4K(3840×2160) and VGA(1920×1080)
- Advanced video detection: motion detect, crossline, intrusion
- Support 1 HDD SATA up to 6TB
- 1 audio in / 1 audio out
- 2×USB, 1×RJ45
- Built-in 4 port switch PoE 50W
- Built-in web service, support CMS(BCS Manager), mobile app BCS(android, iOS), P2P, Onvif
- Power supply DC 48V

BCS-B-NVR0401-4P

4 channel 1 HDD network recorder with built-in PoE switch

Key features:

| | |
|-----------------------|---|
| System | IP |
| Functionality | Real-time view, record, playback, backup, remote access |
| System control | Mouse, network |
| IP channels | 4 |
| Video out | 1×HDMI 4K, 1×VGA 1080P |
| Resolution | HDMI4K: 4K(3840×2160)/30Hz, 1920×1080P/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz VGA: 1920×1080P/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz |
| Multi-screen display | HDMI4K/VGA: 1/4 |
| Recording resolution | 8M/6M/5M/4M/3M/1080P/1.3M/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF |
| Max bandwidth | Incoming: 40Mbps, Outgoing: 80Mbps |
| Decoding | 1-ch@8M, 4-ch@1080P |
| Video compression | H.265+/H265/H.264+/H.264 (IPC through Onvif H.264) |
| Playback | 1/4 |
| Audio | 1 in / 1 out |
| Backup | Flash drive (USB) / Network download |
| Ethernet | 1 Port RJ-45 (10/100Mbps) |
| Remote access | 64 |
| Compatibility | Onvif |
| Video detection | Motion detect, crossline, intrusion |
| HDD | 1×SATA max 6TB |
| Interfaces | 2×USB2.0 |
| PoE | Built-in switch PoE 50W IEEE802.3af/at 4×RJ45(10/100Mbps) |
| Power supply | 48V DC, Power consumption <10W (without HDD and PoE) |
| Working environment | -10°C ~+55°C / 10~90%RH |
| Dimensions and weight | 1U 315×240×48mm (W×D×H) 1kg(without HDD) |

