

BCS-P-5621RSAP-II



2Mpx 20x IR Network PTZ Dome Camera



Key features

- Sensor 1/3" 2Mpx PS CMOS
- Video compression H.265 / H.264 / MJPEG
- Triple video streaming
- 30fps at 2Mpx (1920 × 1080)
- IR-cut filter with auto switch (ICR)
- Digital Noise Reduction 2D/3D
- Functions Defog, D-WDR, AGC, AWB, BLC, HLC, EIS
- Web-service, support BCS-NVR-Point, CMS(BCS Manager), mobile app BCS(iOS, android), P2P
- Intelligent functions: cross line, intrusion, face detect, people counting, auto-tracking, audio detect
- Pan speed 300°/s in preset
- Lens with optical zoom up to 20x
- IR Leds distance up to 100m
- High precision positioning
- 1 alarm in / 1 alarm out
- 1 audio in / 1 audio out
- Protection IP66
- Edge storage microSD do 128GB
- Power supply AC24V/DC24V/PoE
- Working environment -40°C ~ +65°C
- 6 KV surge protection designed for network interface

Specification

Model		BCS-P-5621RSAP-II
Scanning system		Progressive Scan
Sensor		1/3" 2Mpx CMOS
Pixels		1920 × 1080
Min. illumination		Color: 0.01 Lux (F1.5, AGC On.) B/W: 0 Lux (IR On.)
S/N ratio		> 52dB
White balance		(AWB) Auto/Manual
Basic functions	Lens	5.2 ~ 104mm F1.5 ~ F3.0 (20x optical zoom) Angle of view H: 60.19°~3.0°
	Backlight compensation	BLC / HLC / D-WDR
	Shutter	Auto/Manual (1/1 ~ 1/100000s),
	Gain control	(AGC) Auto/Manual
	Noise reduction	2D / 3D - regulation
	Privacy masking	24 areas
	Day/night	IR-cut filter with auto switch (ICR)
Video functions	Compression	H.265 / H.264 / MJPEG
	Resolution	1080P(1920x1080) / 720P(1280x720) / D1(720x576) / 2CIF(704x288) / (640x360) / CIF(352x288)
	Main stream	1080P(1 ~ 30fps)
	Second stream	1080P/720P/D1/2CIF/(640x360)/CIF (1 ~ 30fps)
	Triple stream	D1/2CIF/(640x480)/CIF (1 ~ 30fps)
PTZ Functions	Pan/Tilt Range	PAN: 360° (endless) TILT: -15° ~ +90° auto flip
		PAN: 0.1°/s ~ 240°/s (300°/s preset) TILT: 0.1°/s ~ 160°/s (240°/s preset)
	Pan/Tilt Speed	PAN: 0.1°/s ~ 240°/s (300°/s preset)
		TILT: 0.1°/s ~ 160°/s (240°/s preset)
Automatic Functions	255 presets; 16 tour (with 32 presets); 16 pattern up to 15 min	
Network	Ethernet	RJ-45 (10M/100MBase-TX)
	Protocols	L2TP,IPv4,IGMP,ICMP,ARP,TCP,UDP,D HCP,PPPoE,RTP,RTSP, NTP,FTP,HTTP,SNMP,SIP,802.1x,P2P
	Compatibility	ONVIF(Profile S, Profile G), API
	Mobile	Android, iOS
	Users	Max 10 logged in
Edge storage		microSD up to 128GB
Power supply		24VAC±25% / 24VDC±25% / PoE(IEEE802.3at)
Power consumption		9~42W
Working environment		-40°C ~ +65°C
Weight		5,28 kg
Dimensions		∅227 x 359.4 mm

Dimensions

