


BCS-P-TIP24FSR4-Ai1(-G)

Network bullet camera 4Mpx with lens 2.8mm



- Sensor 1/3" 4Mpx PS CMOS
- Starlight technology
- Compression H.265+/H.264+/MJPEG
- Triple stream coding
- IR cut filter with auto-switch ICR
- Functions AWB, AGC, BLC, HLC, ROI, Defog, WDR(120dB), 2D/3D NR
- Motion detect, privacy masking
- Intelligent functions: perimeter protection, crossline, intrusion
- IR range 40m
- Fixed lens 2.8mm F1.6
- Outside metal casing IP67
- Built-in microphone
- Edge storage microSD 256GB
- Built-in web service, support BCS-NVR, CMS(BCS Manager), mobile app BCS(iOS, android), P2P, Onvif
- Power supply DC12V / PoE 802.3af



BCS-P-TIP24FSR4-Ai1(-G)

Network bullet camera 4Mpx with lens 2.8mm

Video system	IP
Scanning system	Progressive Scan
Sensor	1/3" 4Mpx CMOS
Pixels	2688(H) × 1520(V)
Min. illumination	0.003Lux/F1.6 (Color, AGC On) 0Lux(B/W, IR On)
S/N ratio	> 56dB
Lens	2.8mm F1.6
Focus	Fixed
Angle of view	H: 101.1°, V: 55.3°
DORI	Detect 63m / Observe 25m / Recognize 13m / Identify 6m
White balance	(AWB) Auto/manual
Backlight compensation	BLC / HLC / WDR(120dB)
Shutter	Auto/manual (1~1/100000s)
Gain control	(AGC) Auto/manual
Noise reduction	2D/3D NR
Motion detect	4 areas
Privacy masking	4 areas
Image rotate	Mirror, flip
Day/night	IR cut filter with auto-switch ICR
IR range	40m
Video compression	H.265 / H.265+ / H.264 / H.264+ / MJPEG
Resolution	4M(2688×1520)(2560×1440) / 3M(2304×1296) / 1080P(1920×1080) / 720P(1280×720) / D1(704×576) / (640×360) / 2CIF(704×288) / CIF(352×288)
Main stream	4M/3M/1080P@30fps
Second stream	720P/D1/(640×360)/2CIF/CIF@30fps
Third stream	D1/(640×360)/2CIF/CIF@30fps
Audio	Built-in microphone
Audio compression	G.711
Network	RJ-45 (10/100Mbps)
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, P2P
Compatibility	ONVIF(S/G/T)
Edge storage	microSD 256GB
Users	Max 10 logged in
Mobile	iOS, android
Power supply	DC12V (±25%) / PoE(802.3af)
Power consumption	<4W
Working environment	-30°C ~ +60°C, 10%~90% RH
Casing	Metal, IP67
Weight	0.42kg
Dimensions	156×63mm



BCS-P-TIP24FSR4-Ai1(-G)

Network bullet camera 4Mpx with lens 2.8mm

Adapter
BCS-P-A71(-G)



Adapter
BCS-P-A61(-G)

