

## BCS-V-DI236IR5

IR Network Dome Camera 2Mpx with motozoom lens 2.8~12mm




### Key features:

- Sensor 1/2.8" 2Mpx PS CMOS
- Triple stream coding
- Resolution 1920×1080@25/30fps
- Compression H.265+/H.264+/MJPEG
- IR-cut filter with auto switch (ICR)
- Functions AGC, AWB, AES, BLC, HLC, WDR(120dB), 3D DNR, ROI
- Motion detect, privacy masking
- Intelligent functions: intrusion, crossline, face detect, abandoned/missing object
- Built-in web-service, support BCS-NVR, CMS(BCS Manager), mobile app BCS(iOS, android), P2P, Onvif
- Motozoom lens 2.8~12mm F1.4
- IR range up to 50m
- 1 audio in / 1 audio out
- 1 alarm in / 1 alarm out
- Edge storage microSD up to 128GB
- Outside metal casing IP66, IK10
- Working environment -30°C ~ +60°C
- Power supply DC 12V, PoE



### Dimensions:



## BCS-V-DI236IR5

IR Network Dome Camera 2Mpx with motozoom lens 2.8~12mm

### Specification:

System video	IP
System scanning	Progressive Scan
Sensor	1/2.8" 2Mpx CMOS
Pixels	1920(H) × 1080 (V)
Minimum illumination	Color: 0.005Lux@(F1.2, AGC On), 0.0068 Lux@(F1.4, AGC On), B/W:0Lux
Lens	Motozoom 2.8~12mm F1.4, Angle of view H: 105°~35°, V: 56°~20°
White balance	(AWB) Auto/manual
Backlight compensation	BLC / HLC / WDR(120dB)
Shutter	Auto/manual (1/3~1/100000s)
Gain control	(AGC) Auto/manual
Noise reduction	3D DNR
Day/night	IR-cut filter with auto switch (ICR)
IR range	Up to 50m
Video compression	H.265 / H.265+ / H.264 / H.264+ / MJPEG(second stream)
Resolution	1080P(1920×1080) / 960H(1280×960) / 720P(1280×720) / VGA(640×480) / (640×360) / (352×288) / (352×240) / (320×240)
Main stream	50Hz: 25fps (1920×1080, 1280×960, 1280×720) 60Hz: 30fps (1920×1080, 1280×960, 1280×720)
Second stream	50Hz: 25fps (640×480, 640×360, 320×240) 60Hz: 30fps (640×480, 640×360, 320×240)
Third stream	50Hz: 25fps (1920×1080, 1280×720, 640×360, 352×288) 60Hz: 30fps (1920×1080, 1280×720, 640×360, 352×240)
Audio	1 in / 1 out
Audio compression	G.711/G.722.1/G.726/MP2L2/PCM
Network	RJ-45 (10M/100M)
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, P2P
Alarm	1 in / 1 out
Edge storage	microSD up to 128GB
Compatibility	ONVIF(Profile S, Profile G), ISAPI
Users	Max 32
Mobile	iOS, android
Power supply	DC12V(±25%) / PoE(802.3af)
Power consumption	<9.5W
Working environment	-30°C ~ +60°C, 10%~95% RH
Casing	Metal IP66, IK10
Weight	1.3kg
Dimensions	Φ153.4 × 133.1mm

